

## STANDARD OPTIONS

- Ultra quiet blower inlet and exhaust silencers
- 2" ball valve discharge silencer drain valve
- 2" ball valve final filter drain
- 2 1/2" cam-lock water fill
- Direct drive Omsi transfer case - air shift
- Transfer case shift protection
- (60) 70" Bag filtration w/ air cannon
- Wet and dry operation ( no change over required)
- Weather tight control panel box with master switch,
- Tachometer-Hourmeter, blower discharge temp gauge,
- throttle control, vibrator controls, vacuum relief switch,
- E-stop button and hydraulic pressure gauge.
- PTO driven constant pressure HYD pump
- Electronic backup alarm
- 4" manual vacuum relief valve/ air inlet valve
- 8" air operated relief valve
- Color coded sealed electrical system
- color coded air lines
- Electric vibrator
- Tailgate platform and ladder
- Float level indicator
- 6" flanged decant connection, bottom center
- radial diversion wing
- 8" top inspection port
- 8" vacuum pipe package with 8" dig tube
- Top loading port 8" at rear
- Non skid safety grating
- Cat walk and fold down hand rails for debris body
- Heavy duty boom flange
- S.S. Float ball shut off
- Hydraulic oil tank with sight gauge and shut off valves
- Baghouse / cyclone chamber dump doors with full open doors
- Baghouse / cyclone chamber side access clean out doors
- Rear door and debris tank safety props
- 6" in line vacuum relief valve
- remote pendant control with 55' cord
- 25' grounding cable
- digging lance package w/trigger shut off
- dig tube handle assembly
- rear door vacuum port 45 deg. Elbow
- 2" water tank drain
- 75' retractable handgun reel
- Multi flow water system
- Wireless remote w/ water pump controls, vacuum relief valve
- Grounding cable tying chassis frame, subframe and chassis
- tool box passenger side chassis frame. 24x24x24
- right start training
- Hydrant Wrench
- 5lb fire extinguisher and safety triangles in cab
- LED lights, clearance, back-up, stop, tail and turn.
- ISO 46 hydraulic oil
- camera system rear only
- rear door splash shields
- (1) 2 and (1) 3 jet digging nozzle
- 20 gpm @ 2500 PSI water system
- 6" manual knife gate decant
- 8" 7' telescoping boom
- Sludge circuitry (no pump)
- Hydro excavation cold weather package
- Cold weather recirculation system
- Air purge
- Water heater 400,000 BTU
- Certified weight required

## PAINT

- White to Match Cab
- Standard Black Power Module

## CHASSIS

- 2019 Kenworth T880 Tandem Axle w/ Pusher Chassis, Cummins ISX12, 425 HP Engine, Eaton Fuller FRO-16210C Manual Transmission

#15809

# GUZZLER HXX

