

P/N: 40250iB



- Highest cleaning performance
- **Integrated** data management
- Removal of loose deposits



- Pipe Diameter without skid 6" - 16"
- Pipe Diameter with skid 8" - 16"
- Removal of gravel, debris etc.
- Concrete PVC, PE etc.
- Visual cleaning control

Dimensions without skid	10.4" x 3.7"
Dimensions with skid	10.4" x 6.8"
Min. flow	40 gpm
Max. pressure	3,600 psi
Connection thread	1 - 1 1/4"



- Operating with iOS and Android
- Integrated data management
- User-friendly enz App
- Data management with enz cloud



- Sapphire double glazing
- 12 ultra bright LED's
- IP 68 waterproof
- Wireless quick charge function

BENEFITS

- Productivity: Two in one inspection and cleaning capabilities
- Efficiency: Reduces need to utilize dedicated inspection equipment
- Affordability: Entry level mainline inspection
- Output: Increase inspection footage
- Safety: On demand pipeline assessment



ADVANTAGES

- Reliability: Maintenance free, self-contained camera
- Data Management: Easy to use documentation and sharing capabilities
- Capabilities: Multiple size, configurations, and performance options available
- Usefulness: Easy to train and easy to use.
- Support: Backed by industry leaders in sewer cleaning and inspection products

- Very robust, sapphire glazing
- Compatible with other enz nozzles

Technical data

Battery runtime	> 8h
Battery charging time	80% in 3h
Battery type	Li-Ion
Resolution	HD Ready (720p)
Field of vision	134 degrees
Video format	MP4
Rotation compensation Image	Self-leveling camera
Lighting	12 ultra-bright LED's
Light Flux	5400 Lumen
Camera memory	24 GB (> 22h)
Charging Sstation	Qi (Wireless)
Interface	WiFi (IEEE 802.11 b/g/n)
Camera and lighting glasses	Sapphire double glazing

Hardware Compatibility	Apple iOS 12.2 or newer Android 5.0 or newer with Google Chrome v84 Windows 10 with Google Chrome v84 or newer
-------------------------------	--